

SPECIFICATION

09/744,93

TITLE**THREADED CYLINDRICAL MULTIDISCOID SINGLE OR  
MULTIPLE ARRAY DISC PROSTHESIS**

5

This invention relates to the design and use of a unique disc prosthesis for the lumbar, thoracic and cervical spine.

U.S. Patent 5,674,296 is incorporated by reference.

BACKGROUND OF THE INVENTION

10 Degenerative disc disease including disc herniation may produce disabling symptoms of local pain, radiculopathy or myelopathy in an otherwise clinically stable spine, which proves to be unresponsive to non-surgical treatment. Several surgical treatments are available to address the symptoms of degenerative disc disease when non-invasive therapies are not effective. These surgical treatments include decompression,  
15 discectomy and fusion. These treatments, and in particular the discectomy and fusion procedures, provide relief of clinical symptoms but they do not restore normal or near normal range of motion or cushioning to the affected functional spinal unit (FSU). This can result in acceleration of the degenerative process in spinal discs adjacent to the original surgical operation site. This degenerative process can, in turn, require additional  
20 surgical intervention.

Open surgery and endoscopic techniques are often used to provide access to the targeted intervertebral disc space. Posterior, postero-lateral, and anterior approaches allow placement of instrumentation to facilitate exposure of the degenerated disc and the insertion of bone grafts or fusion cages to accomplish bony fusion.

25 Because of anatomical structure considerations and instrument size restrictions associated with minimally invasive surgical techniques in the anterior spine, the insertion of a functional disc prosthesis equal in size to the natural disc creates risks due to mechanical interferences with critical vascular structures and may prevent safe insertion of the prosthesis.

30 A functional disc prosthesis which provides for a full range of motion of the FSU and for cushioning between two adjacent vertebrae while maintaining stability,

intervertebral body spacing and lordosis, is desirable, more specifically it is an object of the invention to provide a disc prosthesis having a small or narrow profile. The novel exemplary prosthesis is cylindrical in exterior shape, comprised of two longitudinally split halves. Each housing half is separated from the other at all times by disk shaped resilient bodies contained therein, and is strong enough to support the loads to which it shall be subjected during the activities of daily living. The housing contains multiple concave articulation recesses capable of mating with the discoid resilient bodies placed therebetween. The discoid bodies are of smaller diameter than the natural disc they replace, and are positioned in series in the shells or articulation recesses contained in the interior of the cylindrical housing. The cylindrical housing is threaded on its exterior for ease of introduction into, and mechanical stability in, a prepared space in the opposing vertebrae of the FSU. The housing is configured to fit the restrictions imposed by the limited anatomical space available for the surgical placement of the implant, and is small so as to utilize implantation procedures and instrumentation such as those used in an endoscopic procedure.

It is a further object of the invention to provide cylindrical housings of differing size, and resilient bodies contained within, so that when the cylindrically shaped prostheses units are used in parallel, they may facilitate proper positioning of opposing vertebrae.

Another object is to obviate the need for a second surgical site for bone graft harvesting.

And it is a further object of the invention to provide a sheath so as to completely surrounded and enclose the space occupied by the resilient bodies between the two cylindrical housing halves.

Still another object of the invention is to provide a disc prosthesis which will permit motion between the housing halves.

A further object of the intention is to provide a disc prosthesis which will provide for cushioning between the housing halves.

It is a still further object of the invention to provide a disc prosthesis which may be used alone or in parallel array with similar prostheses.

Other objects and advantages of the invention will become apparent to those skilled in the art upon reading the following detailed description and upon reference to the drawings. Throughout the drawings, like reference numerals refer to like parts.

5

#### DESCRIPTION OF THE DRAWINGS

Figure 1 is an isometric view of the novel disc prosthesis.

Figure 2 is a sectional view taken substantially in the plane of line 2-2 in figure

1.

Figure 3 is a sectional view taken substantially in the plane of line 3-3 in figure

10 2.

Figure 4 is an isometric view similar to figure 1 but showing an alternate embodiment of the invention.

Figure 5 is a sectional view taken substantially in the plane of line 5-5 in figure

4.

Figure 6 is a sectional view taken substantially in the plane of line 6-6 in figure

15 5.

Figure 7 is an isometric view of a lower half housing of the invention.

Figure 8 is a top plan view of the lower half housing shown in figure 7.

Figure 9 is a sectional view taken substantially in the plane of line 9-9 in figure

20 8.

Figure 10 is a sectional view taken substantially in the plane of line 10-10 in figure 9.

Figure 11 is a top plan view of a lower half housing similar to figure 8 but showing and alternate embodiment of the invention.

Figure 12 is a sectional view similar to figure 9 but taken substantially in the plane of line 12 - 12 in figure 11.

Figure 13 is an isometric view of the lower half housing shown in figures 11 and 12.

Figure 14 is a sectional view taken substantially in the plane of line 14 - 14 in figure 12.

30

While the invention will be described in connection with a preferred embodiment,

it will be understood that it is not intended to limit the invention to this embodiment. On the contrary, it is intended to cover all alternatives, modifications and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

5 To accomplish the objectives set out above, the novel exemplary disc prosthesis 10 includes, as shown in figures 1 and 4, a cylindrical housing 20. The housing 20 includes an upper half housing 22 and a lower half housing 24. In the embodiment showed in figure 1, an upper fixator wing 26 is welded or otherwise associated with the upper half housing 22, and a lower fixator wing 28 is similarly welded or otherwise  
10 associated with the lower half housing 24. These wings 26, 28 can be used to stabilize the prosthesis to bone, as suggested in U.S. Patent 5,674,296. The wings 26, 28 can be omitted, as suggested in figures 4 - 14.

As particularly shown in figures 2, 3, 5 and 6, a plurality of resilient, viscoelastic discs 41, 42 are interposed between the upper half housing 22 and the lower half housing  
15 24 to maintain the housing halves separate from one another and to provide for a defined range of motion. Alternatively, the discs 41, 42 may be made of a suitable hydrogel. If desired, generally conical bosses or posts 29 can fit into recesses 33 formed in the discs 41, 42 to provide stability and limitation against excessive motion.

The housing 20 has an exterior surface 30 which bears a screw thread shape 31.  
20 This screw thread shape 31 is continuous, and is contiguous from housing half 22 to housing half 24 so that the disc prosthesis can be screwed into a pre-tapped intervertebral space hole formed within between two adjacent vertebrae as, for example, in the human spine. If desired, recesses 35 can be formed to permit bone ingrowth and further stabilization of the device. The housing 20 shape can be that of a right cylinder or it can  
25 be conical.

*Sub*  
*ai*  
30 In accordance with one aspect of the invention, this small or thin profile prosthesis 10 can be created by placing more than one ovoid resilient prosthetic discs 41, 42 within a cylindrical housing 20 of metal, ceramic or polymeric material (the housing 20 having been separated into two halves 22, 24 longitudinally). This small device 10 can be implanted in the spine through a small surgical opening. One device 20 containing two or more discs 41, 42 may be used, or by placing two such devices 20 in parallel, each

containing two or more ovoid discs in series, a full range of motion of the functional spinal unit (FSU) can be achieved. If the discoid material possesses resilient, viscoelastic properties, with the housing being split or otherwise open on its sides with the internally placed ovoid discs maintaining the separation of the upper and lower housing members, a cushioning effect may also be realized. If desired, a flexible sheath or seal can be attached to the housing halves, as by a retaining wire or band, as suggested in U.S. Patent 5,674,296.

As suggested in figures 7 - 10, each ovoid disc 41, 42 may be surrounded by a concave surface 51, 52 formed or contained within the housing, and contoured to accept the upper and lower surface shape of each of the ovoid discs 41, 42 so that the housing 20 comprising the two or more halves or paired shells 23, 24 may slide and/or rotate over the surface of the discs 41, 42 to provide for joint space separation and motion.

As suggested in figures 11-14, a single recess 61 can be provided to accommodate both discs 41, 42. If desired, posts 29 can be provided to limit disc - housing half relative motion.

As noted above, the exterior surface of the split housing 20 has a threaded formation so that it may be screwed into a pre-tapped hole of appropriate size at an intervertebral disc space. When properly screwed into place, the upper half of the threaded housing engages the cephalad vertebral bone inferior end plate and the other half 24 of the threaded housing engages the opposing superior end plate of the caudal vertebral bone when fully inserted. The ovoid discs 41, 42 and their respective concave surfaces in any one housing unit may be of differing size so as to allow for appropriate spinal column curvature, especially when inserted in the anterior/ posterior direction, or they may be the same size in any one housing but differ from the size of the discs in the second housing placed in parallel when inserted from a lateral direction.

The device may be inserted via open or minimally invasive techniques including endoscopy, or by a variety of known surgical approaches where adequate anatomical space is available. Though the prosthesis is inserted as a single threaded cylindrical unit, its final position is such that one half of the housing is left exclusively in contact with the end plate of one vertebral body and the other in the exclusive contact of the opposing vertebral body end plate. The discoid vertebral bodies between the cylindrical housing

1000  
 900  
 800  
 700  
 600  
 500  
 400  
 300  
 200  
 100  
 0